

Dome & PTZ



HV105PT7E120S400

7" HD-IP High Speed Dome Camera
IP66 ,P2P Support, IR Range: 120m 1/3" OV
4MPSensor ,Hi3516A, DWDR, 3D NR,
Main Stream: 4MP@30fps; With IR-CUT
H.264/H.265 Compression

Dome & PTZ



HV105LVDHS800

1/2.5" SONY Starvis Sensor
HISILICON HI3519, WDR; With IR-CUT;
Main Stream: 4K/5M/3M/1080P@30fps
Support Audio I/O ,Support Alarm I/O
Internal POE



HV105PT4E010S200.

4.5" HD-IP Medium Speed Dome Camera 1/2.9"
SONY Low Illumination 2.1MP Sensor Hi3516C,
DWDR, 3D NR Main Stream: 1080P@30fps; With
IR-CUT , IP66, 10X Optical Zoom



HV105LVDHS400W.

1/3" OV Sensor Hi3516D, WDR; With IR-CUT Main
Stream: 4MP@20fps, 3MP/1080P@25fps;
Support WIFI, WIFI Range: No obstacles 300m Max.
IP66, 2.8-12mm Manual Zoom Lens



HV105PT4A110HTC200NS

4.5" Mini High Speed Dome Camera
IR Range: 50m , IP66
1/2.9" SONY CMOS Sensor 2.1MP/1080P
Low Illumination, ICR, 3D NR, 10X Optical Zoom



HV105LIRDQS400W.

1/3" OV Sensor Hi3516D, WDR; With IR-CUT Main
Stream: 4MP@20fps, 3MP/1080P@25fps;
Support WIFI, WIFI Range: No obstacles 300m Max.
IP66, 2.8-12mm Manual Zoom Lens



HV105PT5A018HTC200NS

5" Medium Speed Dome Camera
1/2.9" SONY CMOS Sensor 2.1MP/1080P
Low Illumination, ICR, DNR, 1.8X Optical Zoom



HV105LMDES600.

1/2.9" SONY Sensor,Hi3516D, Low Stream, WDR,
With Internal POE ,With SD Card Slot With Wifi
(Max.300m),3D NR; With IR-CUT 2-Way Audio ,Alarm
I/O ,Support CVBS, Board Lens 1.05mm

Cameras IP/Wifi/POE



HV105LIRDBS300
1/2.8" SONY Starvis Sensor HISILICON Hi3516D,
HDR ; External POE
Main Stream: 3MP /1080P@30fps;
With IR-CUT , 2.8mm Len

Price: 96.90



HV105LBP60SL200.
1/2.8" SONY Starvis Sensor HISILICON Hi3516D,
HDR ; IP66 Main Stream: 1080P@30fps; 3MP HD
Lens, With IR-CUT ,Internal POE , 2.8-12mm Manual
Zoom Lens

Price: 110.12



HV105LBP90S400.
1/3" OV High-resolution CMOS Sensor HISILICON
Hi3516D, WDR; With IR-CUT; Internal POE Main
Stream: 4MP@20fps, 3MP/1080P@30fps , 2.8-
12mm Manual Zoom Lens

Price: 141.75



HV105LIRDCS500.
1/1.8" SONY StarvisSensor HISILICON Hi3516A;
WDR, 3D NR, Low-stream; With IR-CUT; External POE
Main Stream: 5MP/3MP/1080P@30fps, 3.6mm
Board Lens

Price: 220.50

Cameras IP/Wifi/POE



HV105LBB60S500.
1/1.8" SONY Starvis back-illuminated CMOS Sensor
HISILICON Hi3516A; WDR, 3D NR, Low-stream; With
IR-CUT; External POE
Main Stream: 5MP/3MP/1080P@30fps, 3.6mm
Board Lens



HV105LBS40S400.
1/3" OV High-resolution CMOS Sensor HISILICON
Hi3516D, WDR; With IR-CUT; Main Stream:
4MP@20fps, 3MP/1080P@30fps; 5MP HD Lens
With External SD Card Slot (Max. 64GB)
With Internal POE , Board Len 6mm



HV105LV60S400W.
1/3" OV Sensor Hi3516D, WDR; With IR-CUT Main
Stream: 4MP@20fps, 3MP/1080P@25fps;
Support WIFI, WIFI Range: No obstacles 300m Max.
2.8-12mm Manual Zoom Lens



HV105LBH30S400W.
1/3" OV Sensor Hi3516D, WDR; With IR-CUT Main
Stream: 4MP@20fps, 3MP/1080P@25fps;
Support WIFI, WIFI Range: No obstacles 300m Max,
2.8mm Lens

Analog Camera



HV105LBM24CHT100B.
1/4" 1.0MP CMOS Sensor, 720P/960H, With IR-CUT, DWDR, DNR, UTC, OSD , 2.8mm Lens

Analog Camera



HV105LBW60HTC200FSL
1/2.8" SONY 2.1MP Starvis Back-illuminated CMOS Sensor, 1080P/960H, With IR-CUT, WDR, DNR, UTC, OSD With Wall Bracket Add USD2 , Board Lens 6mm



HV105LID90CHT100B.
1/4" 1.0MP CMOS Sensor, 720P/960H, With IR-CUT, DWDR, DNR, UTC, OSD, 2.8-12mm Manual Zoom Lens



HV105LSDCHTC200FSL
1/2.8" SONY 2.1MP Starvis Back-illuminated CMOS Sensor, 1080P/960H, With IR-CUT, WDR, DNR, UTC, OSD, Board Lens 3.6mm



HV105LBQ24CHT200ESL
1/2.8" SONY 2.1MP Starvis Back-illuminated CMOS Sensor, 1080P/960H, With IR-CUT, WDR, 3DNR, Defog, Sense-up, UTC, OSD, 2.8mm



HV105LPRCHTC200ESL
1/2.8" SONY 2.1MP Starvis Back-illuminated CMOS Sensor, 1080P/960H, With IR-CUT, WDR, 3DNR, Defog, Sense-up, UTC, OSD, 3.7mm Taper Pinhole Lens



HV105LBH30CHT200FSL
1/2.8" SONY 2.1MP Starvis Back-illuminated CMOS Sensor, 1080P/960H, With IR-CUT, WDR, DNR, UTC, OSD, 2.8mm



HV105LMCM30CHT200FSL
1/2.8" SONY 2.1MP Starvis Back-illuminated CMOS Sensor, 1080P/960H, With IR-CUT, WDR, DNR, UTC, OSD, 3.7mm Taper Pinhole Lens



HV105LBPACHT130S.
1/3" SONY 1.3MP CMOS Sensor, 960P, Low Illumination, DNR, 2.8mm Lens

Camera IP



HV105LIRDNAL200.

1/2.8" SONY StarvisSensor Ambarella S3L, Low-stream, HDR ; Main Stream: 1080P@30fps; 3MP HD Lens, With IR-CUT , External POE , 2.8mm Lens



HV105LIRDNTSL200.

1/2.8" SONY StarvisSensor HISILICON Hi3516D, HDR ; Main Stream: 1080P@30fps; 3MP HD Lens, With IR-CUT ,External POE, 2.8-12mm Manual Zoom Lens



HV105LDHC20SL200.

1/2.8" SONY Starvis Sensor HISILICON Hi3516D, HDR ; Main Stream: 1080P@30fps; 3MP HD Lens, With IR-CUT ,Internal POE , 2.8mm



HV105LBV40AL200.

1/2.8" SONY Starvis Sensor Ambarella S3L, Low-stream, HDR ; Main Stream: 1080P@30fps; 3MP HD Lens, With IR-CUT,Internal POE , 2.8-12mm Manual Zoom Lens

Analog Camera / PTZ keyboard



HV105LIRDNTHTC200ES.

1/2.9" SONY 2.1MP CMOS Sensor, 1080P/960H, With IR-CUT, Low Illumination, WDR, 3DNR, Defog, Sense-up, UTC, OSD, 2.8-12mm Manual Zoom Lens



HV105LIRDCHTC200ESL.

1/2.8" SONY 2.1MP Starvis Back-illuminated CMOS Sensor, 1080P/960H, With IR-CUT, WDR, 3DNR, Defog, Sense-up, UTC, OSD, 2.8-12mm Manual Zoom Lens



IHV105SDK95.

P PTZ Controller with 3D (Pan/Tilt,Zoom) Joystick for IP PTZ 1MP/2MP/4MP ONVIF 2.4 compatible



HV105SDK45.

MINI HD PTZ Controller with 2D (Pan/Tilt) Joystick for Analog PTZ and AHD/HD-CVI/HD-TVI PTZ

Kits.



HV105NVR2004PGHP1S100 .
4 Channel H.264 POE NVR Kits
1x KT-NVR2004PGHP 4 x LBH30S100
without HDD



HV105XVR2004PGHE10
1/4" OV 1.0MP CMOS Sensor,
ICR, DWDR, DNR, UTC, OSD
1x KT-XVR2004PGH 4 x LIRDLHTC100B
without HDD



HV105WIFI2004PG1S100
4 Channel H.264 1MP WIFI Kits 1x KT-
NVR2004PG1W 4 x LBH30S100W4
without HDD



HV105WIFI2004PG1SE200
4 Channel H.264 2MP WIFI Kits 1x KT-
NVR2004PG1W 4 x LBH30S200W4
without HDD

Kits.



HV105WIFI2008PG1S100
4 Channel H.264 1MP WIFI Kits 1x KT-
NVR2004PG1W 4 x LBH30S200W4
without HDD



HV105PLC2004A1S100
4 Channel H.264 PLC NVR & IP Camera Kits
1x PLC2004A 4 x LBW60S100P , without HDD



HV105PLC2004D2S100
4CH PLC NVR H.264 (Aviation Joint Connector)
4x 720P Outdoor Bullet PLC IP Camera IR
30m, 4x DC12V/1A Power Adapter for PLC IP
Camera, 1x DC12V/2A Power Adapter for PLC
NVR, without HDD

NVR2004PGHP : ARM Cortex A9 Processor 4CH (1920x1080),
Incoming Bandwidth: 24MB, 1 VGA, 1 HDMI, Video Compression H.264

XVR2004PGH :Analog: 4*1080N, Analog+Network: 2*Analog(1080N)
+4*network ,Network: 9*1080P/960P/720P(bandwidth≤46M) , H.264

NVR2004PG1W : 9 Channel(4xWIFI IP Camera + 5xONVIF Wired IP Camera),
1 VGA, 1 HDMI, H.264

PLC2004A : IEEE 1901 and HomePlug AV Compliant ,up to 300m.

LIRDLHTC100B : 1/4"1.0MP CMOS Sensor, AHD/CVI/TVI/CVBS 4 IN 1, 3.6mm
Fixed Lens. IR Distance max 20m, OSD&UTC Support

LBH30S100 : Hi3518EV200, 720P, 1280*720@25fps , Focus Length 3.6mm,
2MP

LBH30S100W4/ LBH30S200W4 :1MP/2MP, 1/2.9"SONY Low Illumination
CMOS Sensor, H.265/H.264 Compression Method, 3.6mm Fixed Lens, IR
Distance 30m Max.

LBW60S100P : 1MP Outdoor Fixed Bullet IP IR 40m ,1/2.8"SONY Starvis Back-
illuminated CMOS Sensor, H.264/H.265 , 6mm Fixed Lens

XVR/NVR



HV105XVR3108A.

8CH H.264 5IN1 XVR 1080P, Support AHD/CVI/TVI/IP/Analog Camera Input, Up to HD 4MP and IP 8MP Resolution Recording, Support HDMI, VGA and CVBS Video Output, Support Max. 8CH HD or 32CH IP Camera Input, Support 2 SATA up to 2TB Capacity



HV105XVR2104A.

5-IN-1: AHD/CVI/TVI/IP/Analog 4M AHD, 3M AHD/TVI 2MP AHD/CVI/TVI 4CH, Network, support ,2 x SATA, P2P HDMI, VGA, USB, Audio without HDD



HV105XVR2104D.

5-IN-1: AHD/CVI/TVI/IP/Analog 5M TVI, 4M/3M AHD/TVI 2M AHD/CVI/TVI 4CH, Network, , P2P HDMI, VGA, USB, Audio,without HDD



HV105NVR9804PG.

4CH H.265/H.264 Incoming Bandwidth: 80MB Hexaplex Operation Simultaneously: Preview, Recording, Playback, Live, Backup Static IP, P2P, Support IE and Special CMS Support Remote View by Smart Phone

XVR/NVR



HV105NVR9804PGHP.

4CH POE H.265 NVR Incoming Bandwidth: 80MB Compression Method: H.265/H.264 Support Remote View by Smart Phone without HDD



HV105NVR9808DP.

8CH POE H.265/H.264 NVR Incoming Bandwidth: 80MB Compression Method: H.265/H.264 Support Remote View by Smart Phone without HDD



HV105NVR9804PGW.

4CH WIFI H.265/H.264 NVR (10M/100M Adaptive Ethernet Interface) Incoming Bandwidth: 80MB WIFI Range: No Obstacles 200m Max. Support Remote View by Smart Phone *without HDD*



HV105LS-RT812.

SWITCH WITH 8-PORT POE 8-PORT 10/100M + 2-PORT 10/100/1000M



HV105LSRT2412:

SWITCH WITH 24-PORT POE 24-PORT 10/100M + 2-PORT Giga WebSwitch



HV105L20NET.

Video Conductor: 0.5mm CCA Jacket: 5.5mm Blue
Remarks: Plug-RJ45, Wiring-568



HV105LS-8H.

1 to 8CH power cable splitter



HV105L18HDC.

DC+BNC for HD-SDI Cameras (Black)



HV105L20DB

DC+BNC for Analog Camera

HV105L20DBR :

DC+BNC+RCA for Analog Camera



HALSECAVISION

4700 W Prospect Rd, Suite 103
Fort Lauderdale, FL 33309, USA

Unit 1201-5 China Resources Building,
No. 26 Harbour Rd, Wanchain, Hong Kong

Av, Romulo Gallegos, Edf. Los Almendros,
Mezzanina, Oficina No.1(Halseca),
Cod Postal 1071, Venezuela

Av. La rotonda, Prime Time Tower, Piso 6
Costa del Este, Cod Postal 080812, Panama

Phone: 561-562-3678
Fax:954-951-6477
Email: info@halsecavision.com